



Selection Table

Lighting

	Series	Va Rating		Phase Switching	Thermal Protection	Min/Max Setting	Available in Black	Fits ALL standard plates	Fits ALL plates	Lamp Pre-heat	Knob Rotation (1)	Knob Switch (2)	Power ON Default (3)	2,3,4,5... Way Dimming	Soft Start	Soft Stop
UNIVERSAL Dimmer	U	500, 750, 1000	Leading Trailing	✓	✓	✓	✓	✗	✓	270deg	✗	ON	✗	✓	✗	✗
MultiWay UNIVERSAL	UW		Leading Trailing	✓	✓	✓	✓	✓	✓	360deg	✓	OFF	✓	✓	✓	✓
Lighting Controller	L	500, 750, 1000, 2000, 3000	Leading	✓	✓	✓	✓	✗	✓	270deg	✗	ON	✗	✓	✗	✗
MultiWay Lighting Controller	LW		Leading	✓	✓	✓	✓	✓	✓	360deg	✓	OFF	✓	✓	✓	✓
Trailing Edge Dimmer	T	500, 750, 1000	Trailing	✓	✓	✓	✓	✗	✗	270deg	✗	ON	✗	✓	✗	✗
MultiWay Trailing Edge Dimmer	TW		Trailing	✓	✓	✓	✓	✓	✗	360deg	✓	OFF	✓	✓	✓	✓
Motor																
Motor Controller	M	350, 500, 1000, 2000, 3000	Leading	✓	✓	✓	✓	✗	✗	270deg	✗	ON	✗	✓	✗	✗
SWITCHED Motor Controller	MS	350, 1000, 3000	Leading	✓	✓	n/a	✓	✗	✗	n/a	✗	ON	✗	✓	✓	✓

NOTE:

- (1) 270deg is a Potentiometer which retains memory after power loss. 360deg is a Rotary encoder with no memory if isolated from the mains.
- (2) Pressing the Rotary Knob will cause the unit to turn On or Off.
- (3) If the product is isolated from the mains (or power loss), upon reconnection, the unit will stay off until the user turns it on.

Phone: (0800) 820 821
Fax: (0800) 002 578
Email: contact@kiwielelectronics.co.nz
Web: www.kiwielelectronics.co.nz